



GF/RF 118

- Wheel Position: Chip & Cut All wheel positions
- For improved or mixed road surface in good and bad conditions
- Good wear-resistance
- Strong cap and carcass design improves the resistance to blowouts and the endurance of the bead
- Improved traction performance
- Good resistance to puncture

Product Number	Tire Size	Pattern	PR	Rim Size	Tread Depth (mm)	Load Index S/D & Speed S	Section Width (mm)	Overall Diameter Hwy/Traction (mm)	Max. Air Single/Dual (kpa)	Load Capacity Single/Dual (kg's)	Qty/40'HC	Price (USD)
63920	8.25R20	GF118	16	6.5	16	137/137 & K	235	855	770/770	128/124		
63901	9.00R20	GF118	16	7.0	15.5	144/142 & K	259	1019	900/900	144/142		
63902	10.00R20	GF118	18	7.5	16.5	149/146 & K	278	1054	930/930	149/146	274 sets	
63903	11.00R20	GF118	18	8.0	17	152/149 & K	293	1085	930/930	152/149	242 sets	
63905	12.00R20	GF118	18	8.5	17.5	154/151 & K	315	1125	830/830	154/151	225 sets	
63919	11.00R22.5	GF118	16	8.0		150/147 & K	293	1085	830/830	150/147		
63924	11R24.5	GF118	16	8.3		149/146 & M						