



# GCA-3

OFF-THE-ROAD



**RUGGED**  
**RELIABLE**  
**RESILIENT**

GCA-3

Size	Load rating	Tube	Code Indication	Approved rim	Tread Depth (mm)	Load index		New tyre inflated dimensions (mm)		Max. Load (kg/LBS@various inflation pressure (kPa/PSI))	
						Single	Dual	Section Width	Overall Diameter	50km/h B	10km/h A2
26.5R25	*	TL	E-3/L-3	22.00/3.0	38.5	184B	202A2	747	1839	9000/19800@350/51	15000/33100@450/65
	**					193B	209A2			11500/25400@450/65	18500/40800@575/83
29.5R25	*	TL	E-3/L-3	25.00/3.5	43	191B	208A2	833	1972	10900/24000@350/51	18000/39700@450/65
	**					200B	216A2			14000/30900@450/65	22400/49400@575/83



- ☑ **Traction Type, Normal Depth Tread**
- ☑ **Non-Directional Pattern**
- ☑ **Great Resistance To Heat Build-Up**
- ☑ **Most Suitable For Haulage Equipment In Coal Mines**
- ☑ **Equally Applicable To Operations On Soft & Muddy Surfaces**

Road Force is a Registered and Associate Brand of Hercules Tire & Rubber Company

\* Data Sheet